



SAFETY DATA SHEET
TROPICAL KILLA ANTI-FOULING - BLUE & BLACK

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME TROPICAL KILLA ANTI-FOULING - BLUE & BLACK
PRODUCT NO. 525/C262/4 & 2
APPLICATION AS A COATING TO DISCOURAGE FOULANT FORMATION ON BOAT HULLS AND MARINE STRUCTURES
SUPPLIER TEAL & MACKRILL LIMITED
LOCKWOOD STREET
HULL
HU2 0HN
+44(0)1482 320194(T)
+44(0)1482 219266(F)
info@teamac.co.uk
CONTACT PERSON Technical Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

2 HAZARDS IDENTIFICATION

Flammable. Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
CLASSIFICATION Xn;R20. Xi;R36/37/38. R43. N;R51/53. R10.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
1,2,4-TRIMETHYLBENZENE	202-436-9	95-63-6	1-5%	R10 Xn;R20 Xi;R36/37/38 N;R51/53
COPPER (I) OXIDE	215-270-7	1317-39-1	10-30%	Xn;R22 N;R50/53
CUMENE	202-704-5	98-82-8	<1%	R10 Xn;R65 Xi;R37 N;R51/53
ETHANOL	200-578-6	64-17-5	<1%	F;R11
ETHYLBENZENE	202-849-4	100-41-4	<1%	F;R11 Xn;R20
MESITYLENE	203-604-4	108-67-8	1-5%	R10 Xi;R37 N;R51/53
METHANOL	200-659-6	67-56-1	<1%	F;R11 T;R23/24/25,R39/23/24/25
NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY	265-185-4	64742-82-1	1-5%	Xn;R65. N;R51/53. R10,R66,R67.
ROSIN	232-475-7	8050-09-7	5-10%	R43
SOLVENT NAPHTHA (PETROLEUM)	265-199-0	64742-95-6	5-10%	Xn;R65. N;R51/53. R10,R66,R67.
SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.	265-191-7	64742-88-7	5-10%	Xn;R65. N;R51/53. R10,R66.
TOLUENE	203-625-9	108-88-3	<1%	F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67
XYLENE	215-535-7	1330-20-7	1-5%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION
Get medical attention if any discomfort continues.

TROPICAL KILLA ANTI-FOULING - BLUE & BLACK

INHALATION

Move into fresh air and keep at rest. Perform artificial respiration if breathing has stopped. Place unconscious person on the side in the recovery position and ensure breathing

INGESTION

Get medical attention immediately! DO NOT INDUCE VOMITING!

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. DO NOT use solvents or thinners

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Immediately flush with plenty of water or eyewash solution for up to 10 minutes. Consult a physician for specific advice.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS

By fire, toxic gases may be formed (CO_x, NO_x). Fire creates: Acrid smoke/fumes of : Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid inhalation of vapours and contact with skin and eyes. Ensure suitable personal protection (including respiratory protection) during removal of spillages in a confined area.

ENVIRONMENTAL PRECAUTIONS

Do not allow to enter drains, sewers or watercourses. Contain spillages with sand, earth or any suitable adsorbent material. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

SPILL CLEAN UP METHODS

Collect with absorbent, non-combustible material into suitable containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Risk of vapour concentration on the floor and in low-lying areas. Use explosion proof electric equipment. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

STORAGE PRECAUTIONS

Keep containers tightly closed. Keep upright. Protect from light, including direct sunrays. Store in closed original container at temperatures between 5°C and 25°C. Store separated from: Oxidising material. Acids. Alkalies.

STORAGE CLASS

Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workshop provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

TROPICAL KILLA ANTI-FOULING - BLUE & BLACK

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
1,2,4-TRIMETHYLBENZENE	WEL				
CUMENE	WEL	25 ppm(Sk)	125 mg/m3(Sk)	50 ppm(Sk)	250 mg/m3(Sk)
ETHANOL	WEL	1000 ppm	1920 mg/m3		
ETHYLBENZENE	WEL	100 ppm(Sk)	441 mg/m3(Sk)	125 ppm(Sk)	552 mg/m3(Sk)
METHANOL	WEL	200 ppm(Sk)	266 mg/m3(Sk)	250 ppm(Sk)	333 mg/m3(Sk)
SOLVENT NAPHTHA (PETROLEUM)	SUP		mg/m3		
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	150 ppm(Sk)	574 mg/m3(Sk)
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit. In case of inadequate ventilation, use air-supplied full-mask.

HAND PROTECTION

Wear protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

HYGIENE MEASURES

Wash promptly with soap & water if skin becomes contaminated. Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Coloured liquid		
COLOUR	Blue or Black		
ODOUR	of solvents		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	1.48 - 1.52 @ 20C	VAPOUR DENSITY (air=1)	heavier than air
VOLATILE BY VOL. (%)	40	VISCOSITY	4.5 Ps @ 25C
FLASH POINT (°C)	38 C approx. CC (Closed cup).	VOLATILE ORGANIC COMPOUND (VOC)	402 g/litre

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and oxidising substances.

TROPICAL KILLA ANTI-FOULING - BLUE & BLACK

MATERIALS TO AVOID

Strong alkalis. Strong acids. Strong oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

No data recorded.

GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

INHALATION

May cause irritation to the respiratory system. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea. Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.

INGESTION

Liquid irritates mucous membranes and may cause abdominal pain if swallowed. May irritate and cause stomach pain, vomiting and diarrhoea. May cause nausea, headache, dizziness and intoxication.

SKIN CONTACT

May be absorbed through the skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

Irritation of eyes and mucous membranes.

ROUTE OF ENTRY

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

There are no data on the ecotoxicity of this product. The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

BIOACCUMULATION

No data available on bioaccumulation.

DEGRADABILITY

No data available.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

DISPOSAL METHODS

Do not allow runoff to sewer, waterway or ground.

WASTE CLASS

When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

14 TRANSPORT INFORMATION

TROPICAL KILLA ANTI-FOULING - BLUE & BLACK



UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT PRODUCT		
UN NO. ROAD	1263	UK ROAD PACK GR.	III
ADR CLASS NO.	1263	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	UN NO. SEA	1263
IMDG CLASS	3	IMDG PACK GR.	III
EMS	F-E, S-E	MARINE POLLUTANT	



15 REGULATORY INFORMATION

LABELLING



Harmful



Dangerous for the environment

CONTAINS

ROSIN

RISK PHRASES

R10	Flammable.
R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S2	Keep out of the reach of children
S13	Keep away from food, drink and animal feeding stuffs.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29/56	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
S37	Wear suitable gloves.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 1988. Health and Safety at Work Act 1974.

TROPICAL KILLA ANTI-FOULING - BLUE & BLACK

ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Rivers (Prevention of Pollution) Act 1961.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138]

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40) Health and Safety at Work Act (As Amended) 1974 Control of Substances Hazardous to Health Regulations 2002 (as amended) Dangerous Substances and Explosive Atmospheres Regulations 2002 [SI 2002: 2776] The Manual Handling Operations Regulations 1992 [SI 1992:2793] This product is approved under the Control of Pesticides Regulations 1986. Product C262/65 - H.S.E. No. 8394

16 OTHER INFORMATION

REVISION COMMENTS

This is first issue. Issued in new format for Reach compliance

ISSUED BY

Technical Dept. (P.E.)

REVISION DATE 26/01/2009

REV. NO./REPL. SDS GENERATED 0

SDS NO. 11000

SAFETY DATA SHEET STATUS

Approved.

DATE Date Printed

SIGNATURE Initials

RISK PHRASES IN FULL

- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R22 Harmful if swallowed.
- R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
- R43 May cause sensitisation by skin contact.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R63 Possible risk of harm to the unborn child.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

TROPICAL KILLA ANTI-FOULING - BLUE & BLACK

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.